



SUBMITTAL INFORMATION

No-Contact Lead-Pak Coupling - (Qx1-xx-NC-NL style)



NO-CONTACT LEAD PIPE PACK JOINT TO FEMALE IRON PIPE THREAD (PATENT 10,371,296)



**Patent
10,371,296**

Due to design variations related to sizing, items may differ from images above.

LEAD-PAK SIZE	FIP SIZE	LENGTH	APPROX. WT. LBS	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
5/8" dbl. extra strong lead (XXS) or 3/4" strong lead (S)	3/4"	2-11/64"	1.2	Q11-33-Q31-23-NC-NL	
1" extra strong lead (XS)	1"	2-1/2"	1.9	Q21-44-NC-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- To attach copper, iron, plastic or PVC to an existing lead service line
- Permanently installed plastic gripper ring and sleeve liner made of acetyl plastic (POM)
- Prevents direct contact of the lead plumbing line with other metallic water system components which can mitigate the possibility of galvanic corrosion

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

10/08/19

Submitted By: