



SUBMITTAL INFORMATION

Retrosetters for Sampling Station - (RETRO-SS-2BHC-NL style)



**NO VALVE INLET BY ANGLE CARTRIDGE DUAL CHECK VALVE WITH
MALE QUICK DISCONNECT FOR SAMPLING STATION OUTLET**



METER SIZE	METER LENGTH	APPROX. HEIGHT	APPROX. WT. LBS.	CATALOG NUMBER	✓SUBMITTED ITEM(S)
5/8"x3/4"	7-1/2"	7-5/16"	4.9	RETRO-SS-2BHC-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Copper conforms to ASTM B75 or B88, UNS C12200
- Style "B" Retrosetter raises the meter from the centerline of the service
- Saddle nuts hold the meter in place for tightening
- All Ford® Retrosetters are assembled with lead-free solder
- Ford® Retrosetters are furnished with four rubber gaskets, one for each meter nut and two for the bottom bar
- Conforms to AWWA C700 for meter threads
- Dual check valve is ASSE 1024 approved
- Sampling station pipe is sold separately

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

10/10/19

Submitted By: