



# SUBMITTAL INFORMATION

## Restrained Flange Adapter - (RFAD-xxxx-DxxY-U style)



RESTRAINED ADAPTER FOR CONVERTING PLAIN END PIPE TO A FLANGE CONNECTION FOR DUCTILE IRON PIPE WITH 304 STAINLESS STEEL HARDWARE AND EPOXY COATING



Nom. PIPE SIZE (IN.)	PIPE OD (IN.)	PART NUMBER	NO. OF RESTRAINT WEDGES	BOLT SIZE (IN.)	BOLT QTY	*MINIMUM PIPE INSERTION DIMENSION "A" (IN.)	PIPE ADJUSTABILITY DIMENSION "B" (IN.)	MAX. DEFLECTION ALLOWANCE	APPROX. Wt. LBS	SUBMITTED ITEM(S)
10	11.10	RFAD-1110-D10Y-U	6	3/4 x 4-1/2	8	4-3/4	3-3/4	5°	80	
12	13.20	RFAD-1320-D12Y-U	8	3/4 x 4-1/2	8	4-3/4	3-3/4	5°	100	

\*Not accounting for beveled, unsquare or deflected pipe ends

### FEATURES

- Sleeve - Carbon steel per ASTM A36
- Flange - Class D AWWA C207, black Armorguard e-coat applied epoxy
- Restraint gland - Ductile iron per ASTM A536, black Armorguard e-coat applied epoxy
- Restraint actuating screws and wedges - Ductile iron per ASTM A536 with auto-tork break away head design, black Armorguard e-coat applied epoxy
- Bolts and nuts - Type 304 stainless steel per ASTM A193 and A194
- Gasket - SBR Rubber per ASTM D2000
- Finish - Fusion bonded epoxy coating
- Rated at 150 PSI
- Certified to ANSI/NSF 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
 P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
 Phone: 260-563-3171 / Fax: 800-826-3487  
 Overseas Fax: 260-563-0167  
[www.fordmeterbox.com](http://www.fordmeterbox.com)

Submitted By: