



SUBMITTAL INFORMATION

Ball Valve Curb Stop - (SI-B41-xxx-HB-34S-AWT-NL style)



**INSULATED - WITH PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET
BY FEMALE IRON PIPE OUTLET, ASSEMBLED WATERTIGHT**



Due to design variations related to sizing, items may differ from images above.

VALVE SIZE	INLET SIZE	OUTLET SIZE	APPROX. LENGTH	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
3/4"	3/4"	3/4"	5-11/16"	2.6	SI-B41-333-HB-34S-AWT-NL	
1"	1"	1"	6"	3.9	SI-B41-444-HB-34S-AWT-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Valve is non-directional and is watertight with flow in either direction.
- Ends are integral or secured with adhesive to prevent unintentional disassembly.
- 300 PSI working pressure
- Handle provides easy cycling of ball valve
- Brass handle attached with bolt and nut

Optional full 360° tee-head rotation. Add "R" to part number.

Example: SI-B41-333R-HB-34S-AWT-NL

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

12/07/23

Submitted By: