

SUBMITTAL INFORMATION

70 Series Tandem Coppersetter - (TVBHC72-xxW-11-xx-NL style)



ANGLE BALL VALVE BY ANGLE CARTRIDGE DUAL CHECK VALVE (5/8" X 3/4" METER)

DOUBLE PURPOSE UNION SWIVEL INLET AND OUTLET



Copporation i art italian							
HEIGHT (INCHES)	APPROX. Wt. Lbs.	CATALOG NUMBER (INSERT SERVICE LINE CONN. SIZE)	✓ SUBMITTED ITEM(S)				
9	8.7	TVBHC72-9W-11-xx-NL					
12	8.9	TVBHC72-12W-11-xx-NL					
15	9.1	TVBHC72-15W-11-xx-NL					
18	9.3	TVBHC72-18W-11-xx-NL					
21	10.0	TVBHC72-21W-11-xx-NL					
24	10.1	TVBHC72-24W-11-xx-NL					
27	11.0	TVBHC72-27W-11-xx-NL					
30	11.3	TVBHC72-30W-11-xx-NL					
33	11.6	TVBHC72-33W-11-xx-NL					
36	11.8	TVBHC72-36W-11-xx-NL					
39	12.0	TVBHC72-39W-11-xx-NL					

Coppersetter Part Number

Tie Bar for 21" and Taller Heights

Adapters for Regulator (MIP by Male Meter Thread)

TVBHC72-42W-11-xx-NL



12.4

CATALOG	METER	ADAPTER	APPROX.
Number	Size	LENGTH	Wt. Lbs.
RA-2-NL	5/8"x3/4"	2-1/16"	0.8

Service Line Size

INLET	OUTLET	SERVICE LINE CONN. SIZE	✓ SUBMITTED ITEM(S)
3/4" D.P. Swivel	3/4" D.P. Swivel	33	
1" D.P. Swivel	1" D.P. Swivel	44	

Note: Ford recommends insert stiffeners when using plastic pipe or tubing

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Copper conforms to ASTM B75, Copper Alloy UNS C12200
- ASSE 1024 approved dual cartridge check valve
- Bracing eye is standard on all 70 Series Coppersetters.
- Tie bar is standard for 21" and taller Coppersetter heights (TVBHC72 Series)
- 13/16" copper risers provide more flow capacity
- · All Ford Setters are assembled with lead-free solder
- Unless specified otherwise, Tandem Coppersetters are designed to hold a water meter in series with a pressure regulator
- Tandem Coppersetters include an "S" tube and a pair of male iron pipe by male meter thread regulator adapters for holding a pressure regulator
- Double Purpose Union Swivel will accommodate male iron pipe threads or flare copper

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

04/07/16

$\overline{}$	_	• • • •]
ธน	nn	nitted	ΙBV