

SUBMITTAL INFORMATION

70 Series Tandem Coppersetter - (TVBHH72-xxW-47-xx-G-NL style)



ANGLE BALL VALVE BY ANGLE DUAL CHECK VALVE (5/8"x3/4" METER)

GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY PACK JOINT FOR PVC PIPE OUTLET



ooppersetter i art italiber							
HEIGHT (INCHES)	APPROX. Wt. Lbs.	CATALOG NUMBER (INSERT SERVICE LINE CONN. SIZE)	✓ SUBMITTED ITEM(S)				
7	6.5	TVBHH72-7W-47-xx-G-NL					
9	6.7	TVBHH72-9W-47-xx-G-NL					
12	6.9	TVBHH72-12W-47-xx-G-NL					
15	7.1	TVBHH72-15W-47-xx-G-NL					
18	7.8	TVBHH72-18W-47-xx-G-NL					
21	8.0	TVBHH72-21W-47-xx-G-NL					
24	8.3	TVBHH72-24W-47-xx-G-NL					
27	8.5	TVBHH72-27W-47-xx-G-NL					
30	8.8	TVBHH72-30W-47-xx-G-NL					
33	9.1	TVBHH72-33W-47-xx-G-NL					
36	9.3	TVBHH72-36W-47-xx-G-NL					
39	9.6	TVBHH72-39W-47-xx-G-NL					
42	9.9	TVBHH72-42W-47-xx-G-NL					

Coppersetter Part Number



Adapters for Regulator (MIP by Male Meter Thread)

CATALOG	Meter	ADAPTER	APPROX.
Number	Size	LENGTH	Wt. Lbs.
RA-2	5/8"x3/4"	2-1/16"	.8

Service Line Size

INLET	OUTLET	SERVICE LINE CONN. SIZE	✓ SUBMITTED ITEM(S)
3/4" (CTS) GJ Nut	3/4" PVC PJ Nut	33	
1" (CTS) GJ Nut	1" PVC PJ Nut	44	

Note: Ford recommends insert stiffeners when using plastic pipe or tubing.

Note: Ford Pack Joints for PVC are recommended for Schedule 40 and Schedule 80 pipe only

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (UNS NO C89833)
- The product has the letters "NL" cast into the main body for proper identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- Bracing eye is standard on all 70 Series Coppersetters
- Tie bar is standard for 18" and taller Coppersetter heights (TVBHH72 Series)
- 13/16" Copper Risers provide more flow capacity
- All Ford Setters are assembled with lead-free solder.
- Unless specified otherwise, Tandem Coppersetters are designed to hold a water meter in series with a pressure regulator
- Tandem Coppersetters include an "S" tube and a pair of male iron pipes by male meter thread regulator adapters for holding a pressure regulator
- Copper conforms to ASTM B-75 Copper Alloy #122
- ASSE 1024 approved Dual Check Valve

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



Tie Bar for 18" and Taller Heights

The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 http://www.fordmeterbox.com

02/27/13

_	-		_	_
Sı.	ıhr	nitte	M	R۱