



# SUBMITTAL INFORMATION

## "U" Branch Piece - (U44-43-65-AWT-G-NL style)



GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY  
TWO GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) OUTLETS, ASSEMBLED WATERTIGHT



DESCRIPTION		LENGTH (IN.)	SPACING (IN.)	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
GRIP JOINT INLET	GRIP JOINT OUTLETS					
1"	Two - 3/4"	3-15/16	6-1/2	2.1	U44-43-65-AWT-G-NL	

\* 7-1/2" spacing is standard and will be provided unless otherwise specified.

**Note:** Ford recommends using insert stiffeners with plastic pipe or tubing.

### FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Ends are integral or secured with adhesive to prevent unintentional disassembly

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
Phone: 260-563-3171 / Fax: 800-826-3487  
Overseas Fax: 260-563-0167  
[www.fordmeterbox.com](http://www.fordmeterbox.com)

12/17/25

Submitted By: