



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1300-C-xx-Q-U style)




SERIES 1300-C 14" - 36" RESTRAINT (WITH 316 STAINLESS STEEL HARDWARE) FOR PVC PIPE OR HDPE AND MECHANICAL JOINT FITTINGS

1300 SPLIT RESTRAINT



1300 WITH MJ FITTING



NOM. PIPE SIZE	OD (IN.)	CATALOG NO.	A	B APPROX.	C MAX	RESTRAINING BOLTS / RODS		CLAMPING BOLTS		BC MIN	BC MAX	APPROX. WEIGHT LBS.	✓ SUBMITTED ITEM(S)
						No.	SIZE	No.	SIZE				
14"	15.30	UFR1300-C-14-Q-U	4"	22-3/4"	15"	6	3/4" x 17"	4	7/8" x 7"	18.44"	20.44"	72.5	
16"	17.40	UFR1300-C-16-Q-U	4"	24-5/8"	15"	6	3/4" x 17"	4	7/8" x 5"	20.50"	22.50"	68.0	
18"	19.50	UFR1300-C-18-Q-U	5"	26-3/4"	15"	8	3/4" x 17"	4	1" x 7"	22.63"	24.63"	109.0	
20"	21.60	UFR1300-C-20-Q-U	5"	29"	22"	8	3/4" x 24"	4	1" x 7"	24.75"	26.75"	144.0	
24"	25.80	UFR1300-C-24-Q-U	5"	33-5/32"	22"	12	3/4" x 24"	4	1" x 7"	28.88"	30.88"	220.0	
30"	32.00	UFR1300-C-30-Q-U	10"	40-5/8"	22"	12	1" x 24"	6	1-1/8" x 9"	36.13"	38.13"	325.0	
36"	38.30	UFR1300-C-36-Q-U	10"	48"	22"	12	1" x 24"	6	1-1/8" x 9"	42.50"	45.50"	360.0	

Note: For DR18, longer rods may be required. Please contact factory for more information.

FEATURES

- Fabricated carbon steel per ASTM A36 or cast ductile iron per ASTM A536
- 360° contact and support of the pipe wall
- Ideal companion for push-on fittings with restraint ears
- Rods, clamping bolts and nuts (included) are type 316 stainless steel per ASTM A193 and ASTM A194
- Rated at full-rated pressure of any class of PVC pipe or HDPE (SDR9 through SDR26) with the use of a proper insert stiffener; minimum 2:1 safety factor
- Coating: Black shop coat - NSF61 approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com



Submitted By:

07/21/20