



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1300-P-15-I style)



SERIES 1300-P 15" RESTRAINT DEVICE FOR SDR35 SEWER PIPE



NOM PIPE SIZE	PVC PIPE WITH DI PIPE OD STYLE 1300-P		A	B APPROX	C MAX	RESTRAINING RODS		CLAMPING BOLTS		BC MIN	BC MAX	APPROX. WT. LBS.	✓SUBMITTED ITEM(S)
	OD	CATALOG No.				QTY. D	SIZE E	QTY. F	SIZE G				
15"	15.30	UFR1300-P-15-I	4"	22-5/16"	15"	4	3/4" x 17"	4	7/8" x 7"	18.50"	20.50"	60.0	

FEATURES

- 15" size: cast ductile iron per ASTM A536 grade 65-45-12
- 360° contact and support of the pipe wall
- Rods (included) are high strength, low alloy steel per ANSI / AWWA C111 / A21.11
- 50 psi rated working pressure with a 2:1 safety factor
- Black epoxy coating

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com



05/11/18

Submitted By: