



SUBMITTAL INFORMATION

Uni-Flange® Restraint (*UFR1300-P-x-U style*)



SERIES 1300-P RESTRAINT DEVICE FOR SEWER PIPE



NOM PIPE SIZE (IN.)	SEWER PIPE OD STYLE 1300-P		A (IN.)	B.C. (IN.)	C (IN.)	RESTRAINING BOLTS		CLAMPING BOLTS		APPROX. WT. LBS.	✓ SUBMITTED ITEMS
	OD (IN.)	CATALOG No.				No. D	SIZE E (IN.)	No. F	SIZE G (IN.)		
4	4.22	UFR1300-P-4-U	8-57/64	7-1/2	4-59/64	2	3/4 x 7	2	1/2 x 2-1/4	4.9	
6	6.28	UFR1300-P-6-U	10-57/64	9-1/2	6-63/64	2	3/4 x 7	2	1/2 x 2-1/4	5.3	
8	8.40	UFR1300-P-8-U	13-9/64	11-3/4	9-3/32	2	3/4 x 7	2	1/2 x 2-1/4	5.7	
10	10.50	UFR1300-P-10-U	15-23/64	14	11-29/64	2	3/4 x 7	2	1/2 x 2-1/4	7.2	
12	12.50	UFR1300-P-12-U	18	16-1/4	13-29/64	2	3/4 x 7	2	1/2 x 2-1/4	8.0	

FEATURES

- Carbon steel per ASTM A36 black e-coat
- Clamping bolts and nuts - Grade 5, zinc-plated
- 360° contact and support of the pipe wall
- T-bolts and nuts (included) - High strength, low alloy steel ANSI / AWWA C111.
- Rated at 50 psi with a 2:1 safety factor

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com



09/24/24

Submitted By: