


## SUBMITTAL INFORMATION





SERIES 1300-S 2" - 12" RESTRAINT (WITH BLUE FLUOROCARBON-COATED HARDWARE) FOR PVC PIPE OR HDPE PIPE AND MECHANICAL JOINT / PUSH-ON FITTINGS



Nom. Pipe Size	OD (ln.)	Catalog Number	A	B Approx.	C Max	RESTRAINING BOLTS / RODS				BC Min	BC Max	APPROX. WEIGHT	✓ SUBMITTED
						No.	Size	No.	Size	IVIIN	IVIAX	LBS.	İTEMS
2"	2.38	UFR1300-S-2-RB-I	1-1/8"	6-3/8"	4"	2	5/8" x 5"	2	5/8" x 3-1/2"	4.38"	4.75"	6.3	
2-1/2"	2.88	UFR1300-S-25-RB-I	1-1/8"	6 -7/8"	4"	2	5/8" x 5"	2	5/8" x 3-1/2"	5.13"	5.38"	6.5	
3"	3.50	UFR1300-S-3-RB-I	1-1/8"	7-5/8"	4"	2	5/8" x 5"	2	5/8" x 3-1/2"	5.81"	6.19"	7.4	
4"	4.50	UFR1300-S-4-RB-I	1-1/8"	9-1/8"	6"	2	3/4" x 7"	2	5/8" x 3-1/2"	7.13"	7.50"	8.5	
6"	6.63	UFR1300-S-6-RB-I	1-1/8"	11-1/8"	6"	2	3/4" x 7"	2	5/8" x 3-1/2"	9.13"	9.50"	10.0	
8"	8.63	UFR1300-S-8-RB-I	1-1/4"	14-7/16"	6"	2	3/4" x 7"	2	3/4" x 4"	11.75"	12.75"	15.5	
10"	10.75	UFR1300-S-10-RB-I	1-3/8"	16-5/8"	6"	4	3/4" x 7"	2	7/8" x 5"	13.50"	15.00"	26.5	
12"	12.75	UFR1300-S-12-RB-I	1-3/8"	19-1/4"	6"	4	3/4" x 7"	2	7/8" x 5"	15.63"	17.63"	28.5	

## **FEATURES**

- Cast ductile iron per ASTM A536 grade 65-45-12
- Black e-coat epoxy coating (NSF 61 approved) with gray painted top coat for identification
- 360° contact and support of the pipe wall
- · Ideal companion for push-on fittings with restraining ears
- T-Bolts (included) High strength, low alloy steel ANSI / AWWA C111 / A21.11 with blue fluorocarbon-coating
- · Side Clamping Bolts and Nuts Grade 5 with blue fluorocarbon-coating
- Rated at full-rated pressure of any class of PVC pipe or HDPE (SDR 9 through SDR26 with the use of a proper insert stiffener); minimum 2:1 safety factor

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



## The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com



Submitted By:

07/28/20