



# SUBMITTAL INFORMATION

## Uni-Flange® Restraint - (UFR1350-C-x-X-I style)




### 4" - 12" SERIES 1350-C RESTRAINT HARNESS FOR PVC PIPE BELL WITH 304 STAINLESS STEEL HARDWARE

1350 Back-Up Ring



1350 Assembly



NOM. PIPE SIZE	OD (IN.)	CATALOG NO.	A	B APPROX.	RESTRAINT BOLTS	RESTRAINT CLAMPING BOLTS	MAX BELL CLEARANCE	APPROX. WEIGHT LBS	✓ SUBMITTED ITEMS
4"	4.80	UFR1350-C-4-X-I	1-1/8"	9-1/8"	(2) 3/4" x 9"	(2) 5/8" x 3-1/2"	6.63"	12.5	
6"	6.90	UFR1350-C-6-X-I	1-1/8"	11-7/8"	(2) 3/4" x 9"	(2) 5/8" x 3-1/2"	8.63"	16.2	
8"	9.05	UFR1350-C-8-X-I	1-1/4"	14-5/8"	(2) 3/4" x 12"	(2) 3/4" x 4"	12.13"	25.5	
10"	11.10	UFR1350-C-10-X-I	1-3/8"	16-5/8"	(4) 3/4" x 17"	(2) 7/8" x 5"	14.13"	41.5	
12"	13.20	UFR1350-C-12-X-I	1-3/4"	19-7/8"	(4) 3/4" x 17"	(2) 7/8" x 5"	16.75"	48.5	

## FEATURES

- Split ring restraint - Ductile iron per ASTM A536, grade 65-45-12
- Back-up ring - Ductile iron per ASTM A536, grade 65-45-12
- T-Bolts / rods, clamping bolts and nuts (included) - Type 304 stainless steel per ASTM A193 and A194
- Rated at full-rated pressure for most PVC pipe, minimum 2:1 safety factor  
- Not recommended for use on AWWA C900, DR-14 PVC pipe (use Series 1390)
- Black e-coat epoxy coating - NSF 61 approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



**The Ford Meter Box Company, Inc.**  
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
Phone: 260-563-3171 / Fax: 800-826-3487  
Overseas Fax: 260-563-0167  
www.fordmeterbox.com



09/01/20

Submitted By: