



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1350-C-x-X-U100 style)




4" - 12" UNI-FLANGE SERIES 1350-C RESTRAINT HARNESS FOR PVC BELL JOINTS WITH 304 STAINLESS STEEL HARDWARE

1350 Back-Up Ring



1350 Assembly



NOM. PIPE SIZE	OD (IN.)	CATALOG NUMBER	A	B APPROX.	RESTRAINT BOLTS	RESTRAINT CLAMPING BOLTS	MAX BELL CLEARANCE	APPROX. WEIGHT LBS	✓ SUBMITTED ITEMS
4"	4.80	UFR1350-C-4-X-U100	1-1/8"	9-1/8"	(2) 3/4" x 9"	(2) 5/8" x 3-1/2"	6.63"	13.0	
6"	6.90	UFR1350-C-6-X-U100	1-1/8"	11-7/8"	(2) 3/4" x 9"	(2) 5/8" x 3-1/2"	8.63"	17.2	
8"	9.05	UFR1350-C-8-X-U100	1-1/4"	14-5/8"	(2) 3/4" x 12"	(2) 3/4" x 4"	12.13"	26.0	
10"	11.10	UFR1350-C-10-X-U100	1-3/8"	16-5/8"	(4) 3/4" x 17"	(2) 7/8" x 5"	14.13"	45.5	
12"	13.20	UFR1350-C-12-X-U100	1-3/4"	19-7/8"	(4) 3/4" x 17"	(2) 7/8" x 5"	16.75"	52.0	

FEATURES

- Split ring restraint - Ductile iron per ASTM A536, Grade 65-45-12
- Back-up ring - Ductile iron per ASTM A536, grade 65-45-12
- T-bolts / rods, side clamping nuts and bolts (included) - Type 304 stainless steel per ASTM A193 and ASTM A194
- Rated at full-rated pressure for most PVC pipe, minimum 2:1 safety factor
 - Not recommended for use on AWWA C900, DR-14 PVC pipe (use Series 1390)
- Black e-coat epoxy coating - NSF 61 approved
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com



12/18/20

Submitted By: