



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1360-S-xx-xxxx-U style)



SERIES 1360-S 14"-24" RESTRAINT HARNESS FOR STEEL SIZE PVC PIPE AND PRESSURE FITTINGS




NOM. PIPE SIZE	OD (IN.)	CATALOG NUMBER	BACK-UP RING		RESTRAINT RODS	RESTRAINT CLAMPING BOLTS	BACKUP RING CLAMPING BOLTS	APPROX. WEIGHT LBS.	✓ SUBMITTED ITEMS
			A	*B APPROX.					
14"	14.00	UFR1360-S-14-xxxx-U	4"	24-1/4"	(6) 3/4" x 30"	(4) 7/8" x 7"	(4) 7/8" x 7"	122	
16"	16.00	UFR1360-S-16-xxxx-U	4"	25-1/4"	(6) 3/4" x 30"	(4) 7/8" x 7"	(4) 7/8" x 7"	130	
18"	18.00	UFR1360-S-18-xxxx-U	5"	27-3/4"	(8) 3/4" x 30"	(4) 1" x 7"	(4) 7/8" x 7"	163	
20"	20.00	UFR1360-S-20-xxxx-U	5"	30"	(8) 3/4" x 30"	(4) 1" x 7"	(4) 1" x 7"	235.5	
24"	24.00	UFR1360-S-24-xxxx-U	5"	34-3/4"	(12) 3/4" x 36"	(4) 1" x 7"	(4) 1" x 7"	293	

*These are approximate dimensions. Dimensions are dependent on the bell run O.D.

Note: Bell run O.D. and pipe manufacturer are required when ordering.

Supply bell run outside diameter with order for units 10" and larger.



FEATURES

- Split ring restraint and split back-up ring fabricated from carbon steel per ASTM A36
- Rods (included) - High strength, low alloy steel per ANSI/AWWA C111/A21.11
- Side clamping nuts and bolts - Grade 5 zinc plated
- Rated at full-rated pressure of any class PVC pipe, minimum 2:1 safety factor
- Coating: Black shop coat - NSF 61 approved, gray topcoat for identification purposes

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com



09/14/20

Submitted By: