



SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1390-C-xx-U style)




SERIES 1390-C RESTRAINT HARNESS FOR PVC PIPE OR HDPE BELL JOINTS

1300 SPLIT RESTRAINT



1390 ASSEMBLY



NOM. PIPE SIZE (IN.)	OD (IN.)	CATALOG NUMBER	A (IN.)	B APPROX. (IN.)	C MAX (IN.)	RESTRAINT BOLTS / RODS NUMBER AND SIZE (IN.)	CLAMPING BOLTS NUMBER AND SIZE (IN.)	MAX BELL CLEARANCE (IN.)	APPROX. WEIGHT LBS	✓ SUBMITTED ITEM(S)
14	15.30	UFR1390-C-14-U	4	22-3/4	28	(6) 3/4 x 30	(4) 7/8 x 7	19.56	136	
16	17.40	UFR1390-C-16-U	4	24-5/8	28	(6) 3/4 x 30	(4) 7/8 x 5	21.63	135	
18	19.50	UFR1390-C-18-U	5	26-3/4	28	(8) 3/4 x 30	(4) 1 x 7	23.75	206	
20	21.60	UFR1390-C-20-U	5	29	34	(8) 3/4 x 36	(4) 1 x 7	25.88	263	
24	25.80	UFR1390-C-24-U	5	33-5/32	34	(12) 3/4 x 36	(4) 1 x 7	30.00	406	
30	32.00	UFR1390-C-30-U	10	40-5/8	46	(12) 1 x 48	(6) 1-1/8 x 9	37.00	601	
36	38.30	UFR1390-C-36-U	10	48	46	(12) 1 x 48	(6) 1-1/8 x 9	44.38	672	
42	44.50	UFR1390-C-42-U	10	57-3/16	70	(18) 1-1/4 x 52	(8) 1-1/8 x 9	51.75	981	
48	50.80	UFR1390-C-48-U	10	63-5/8	70	(22) 1-1/4 x 52	(8) 1-1/8 x 9	58.00	1021	

Note: For DR18, longer rods may be required. Please contact factory for more information.

FEATURES

- Fabricated carbon steel per ASTM A36 or cast ductile iron per ASTM A536
- Rods (included) - high strength, low alloy steel per ANSI / AWWA C111 / A21.11
- Side clamping nuts and bolts - Grade 5, zinc plated
- Rated at full-rated pressure of any class of PVC pipe or HDPE, minimum 2:1 safety factor
- Installation on HDPE (SDR9 through SDR 26) requires use of a properly sized insert stiffener
- Finish - Shop coat - NSF 61 certified

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com



06/03/25

Submitted By: