
SUBMITTAL INFORMATION

Uni-Flange® Restraint - (UFR1390-P-x-X-U100 style)



SERIES 1390-P RESTRAINT HARNESS FOR SEWER PIPE BELL JOINTS



Nom Pipe Size	SEWER PIPE OD STYLE 1390-P		A (In.)	B.C. (In.)	C (In.)	RESTRAINTS BOLTS / RODS		CLAMPING BOLTS PER GLAND		APPROX.	✓ SUBMITTED
(IN.)	OD (In.)	CATALOG NO.	1			No.	SIZE (IN.)	No.	SIZE (IN.)	TT II EBO.	
4	4.22	UFR1390-P-4-X-U100	8-57/64	7-1/2	4-59/64	2	3/4 x 17	2	1/2 x 2-1/4	8.2	
6	6.28	UFR1390-P-6-X-U100	10-57/64	9-1/2	6-63/64	2	3/4 x 17	2	1/2 x 2-1/4	9.0	
8	8.40	UFR1390-P-8-X-U100	13-9/64	11-3/4	9-3/32	2	3/4 x 17	2	1/2 x 2-1/4	10.1	
10	10.50	UFR1390-P-10-X-U100	15-23/64	14	11-29/64	2	3/4 x 17	2	1/2 x 2-1/4	12.9	
12	12.50	UFR1390-P-12-X-U100	18	16-1/4	13-29/64	2	3/4 x 17	2	1/2 x 2-1/4	14.5	

FEATURES

- Carbon steel per ASTM A36, black e-coat
- Clamping bolts and nuts Type 304 stainless steel per ASTM A193 and A194
- 360° contact and support of the pipe wall
- Restraining rods (Included) and nuts Type 304 stainless steel per ASTM A193 and A194
- Rated at 50 psi with a 2:1 safety factor
- 100% manufactured in the United States of America

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com



Submitted By:

09/17/24