



SUBMITTAL INFORMATION


Uni-Flange Retainer (UFR1455-D-x-I style)



WEDGE ACTION SERIES 1455-D SOLID RESTRAINT WITH SPLIT BACK UP RING ASSEMBLY FOR DUCTILE IRON PIPE BELL JOINT



WEDGE / ACTUATING SCREW DETAIL



Wedges

Ductile iron wedges are heat-treated to a hardness of 370 BHN minimum

1. Auto-tork breakaway head, 1-1/4" across the flat (same as 3/4" heavy hex nut)
2. 5/8" hex-head, operating screw
3. Rubber spacer (positions wedge during assembly)
4. Wedge

NOM. PIPE SIZE	PIPE O.D.	RODS			PRESSURE RATING (PSI)	*MAX. BELL DIA.	APPROX. Wt. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
		No.	LENGTH	DIA.					
3"	3.96	4	14"	5/8"	350	5.50	12	UFR1455-D-3-I	
4"	4.80	4	17"	3/4"	350	6.62	20	UFR1455-D-4-I	
6"	6.90	6	17"	3/4"	350	8.62	29	UFR1455-D-6-I	
8"	9.05	6	17"	3/4"	350	10.88	35	UFR1455-D-8-I	

* Connecting rods WILL NOT CLEAR a pipe bell with a maximum diameter larger than the listed measurement.

FEATURES

- Gland: Ductile iron per ASTM A536, grade 65-45-12
- Split back-up ring: Ductile iron per ASTM A536 grade 65-45-12
- Wedge actuating screws: Ductile iron per ASTM A536, grade 65-45-12
- Wedge: Ductile iron per ASTM A536 heat treated to hardness of 370 BHN minimum
- Coating: Black Armorguard e-coat applied epoxy
- Restraining rods and nuts: High strength low alloy steel per ASTM A242 (Optional blue fluorocarbon or stainless steel)
- 2:1 safety factor at rated working pressure; 3"-8" - 350 PSI RWP
- New installations only

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

11/10/17

Submitted By: