



SUBMITTAL INFORMATION

Uni-Flange® Split Restraint (*UFR1490-D-x-RB-U style*)



WEDGE ACTION SERIES 1490-D SPLIT RESTRAINT WITH SPLIT BACK UP RING ASSEMBLY FOR DUCTILE IRON PIPE BELL JOINT



NOM. PIPE SIZE	PIPE O.D. (IN.)	RODS			PRESSURE RATING (PSI)	*MAX. BELL DIA. (IN.)	APPROX. WT. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
		No.	LENGTH	DIA.					
14"	15.30	10	24"	3/4"	300	17.88	117.4	UFR1490-D-14-RB-U	
16"	17.40	12	24"	3/4"	300	20.12	135.0	UFR1490-D-16-RB-U	
18"	19.50	12	24"	3/4"	200	22.38	151.6	UFR1490-D-18-RB-U	
20"	21.60	14	24"	3/4"	200	24.62	169.6	UFR1490-D-20-RB-U	
24"	25.80	16	24"	3/4"	200	29.12	187.8	UFR1490-D-24-RB-U	
30"	32.00	20	24"	1"	200	35.80	480.7	UFR1490-D-30-RB-U	
36"	38.30	24	24"	1"	200	42.60	602.8	UFR1490-D-36-RB-U	

* Connecting rods WILL NOT CLEAR a pipe bell with a maximum diameter larger than the listed measurement.

FEATURES

- Split gland: Ductile iron per ASTM A536, grade 65-45-12
- Wedge actuating screw: Ductile iron per ASTM A536, grade 65-45-12
- Split back-up ring: Ductile iron per ASTM A536, grade 65-45-12
- Wedge: Ductile iron per ASTM A536 heat treated to hardness of 370 BHN minimum
- Restraining Rods: High-strength low alloy steel per ASTM A242, blue fluorocarbon coated
- Coating: Black e-coat epoxy - NSF61 approved
- New or existing installations
- 2:1 safety factor at rated working pressure; 14"-16" - 300 PSI RWP, 18"-36" - 200 PSI RWP

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
www.fordmeterbox.com

03/20/20

Submitted By: