
SUBMITTAL INFORMATION

Uni-Flange Split Restraint (*UFR1490-D-xx-RB-XL-I style*)



WEDGE ACTION SERIES 1490-D-XL SPLIT RESTRAINT WITH SPLIT BACK UP RING ASSEMBLY FOR CLASS C & D GREY IRON PIPE WITH BLUE FLUOROCARBON-COATED ACCESSORIES



Nом.	PIPE O.D. (In.)	Rods			PRESSURE	*Max.	Approx.	CATALOG	✓ SUBMITTED
PIPE SIZE (IN.)		No.	LENGTH (In.)	DIA. (IN.)	RATING (PSI)	BELL DIA. (IN.)	WT. LBS.	NUMBER	ITEM(S)
10	11.10	8	24	3/4	350	13.12	56.0	UFR1490-D-10-RB-XL-I	
12	13.50	8	24	3/4	350	16.38	62.0	UFR1490-D-12-RB-XL-I	
16	17.63	12	24	3/4	300	20.12	135.0	UFR1490-D-16-RB-XL-I	

^{*} Connecting rods WILL NOT CLEAR a pipe bell with a maximum diameter larger than the listed measurement.

FEATURES

- Split gland Ductile iron per ASTM A536, grade 65-45-12
- Wedge actuating screw Ductile iron per ASTM A536, grade 65-45-12
- Split back-up ring Ductile iron per ASTM A536, grade 65-45-12
- Wedge Ductile iron per ASTM A536 heat treated to hardness of 370 BHN minimum
- Restraining Rods High strength, low alloy steel per ASTM A242, blue fluorocarbon coated
- Finish Epoxy coating
- 2:1 safety factor at rated working pressure; 10"-12" 350 PSI RWP, 14"-16" 300 PSI RWP

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.

07/30/25



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

43