
SUBMITTAL INFORMATION





42" & 48" SERIES UFR1500-C MECHANICAL JOINT RESTRAINT FOR C900 PVC



Nom. PIPE SIZE (IN.)	PIPE O.D. (IN.)	CATALOG NUMBER	No. of Wedges	APPROX. WEIGHT (LBS.)	P (IN.)	C (In.)	D (ln.)	F (In.)	J (ln.)	PRESSURE RATING C900 DR25	✓ SUBMITTED ITEM(S)
42	44.50	UFR1500-CA-42-I	28	476	53.9	45.79	5.68	44.79	50.62	165 PSI	
48	50.80	UFR1500-CA-48-I	32	573	60.2	52.09	5.67	51.09	57.50	165 PSI	

FEATURES

- The Series 1500 can be used on AWWA C900 PVC
- Auto-Tork actuating screws with heads specially designed to twist off at the correct installation torque, leaving a hex head for future system maintenance or removal
- High strength, low alloy t-bolts and nuts per AWWA C111
- Uni-Seal gasket SBR rubber per ASTM D2000
- · Series 1500 eliminates the need to pour expensive and time consuming concrete thrust blocks
- Restraining segments are mechanically retained in pockets
- Gland, screws and segments are black epoxy coated using the e-coat process
- Gland colored red for identification purposes
- Shipped with Uni-Seal gasket, mechanical joint gland and high strength, low alloy t-bolts and nuts

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

09/11/24

Submitted By: