

SUBMITTAL INFORMATION


Uni-Flange® Series Casing Spacers - (UFRCS1300-C-xx-U style)




CASING SPACERS FOR SUPPORT OF C900 PVC PIPE SIZE 10" AND 12" PIPE BARRELS

UFRCS1300







CASING SPACER FOR SUPPORT OF PIPE BARREL - UFRCS1300

Nom. Pipe Size	ACTUAL PIPE O.D.	CATALOG NUMBER	APPROX. SHIPPING WEIGHT	A	B (Approx.)	C Min.Casing Size (ID)	RUNNER QTY.	✓ SUBMITTED ITEMS
*10"	11.10"	UFRCS1300-C-10-U	29.4	1-3/8"	19-3/4"	21.5"	4	
*12"	13.20"	UFRCS1300-C-12-U	32.2	1-3/8"	21-7/8"	23"	4	

^{*} Suitable for use on ductile iron pipe at a reduced pressure rating.

FEATURES

- High strength ductile iron, ASTM A536, 65,000 psi tensile strength, 45,000 psi yield strength, 12% elongation capability. (Grade 65-45-12)
- Clamping bolts / nuts SAEJ 429, grade 5
- Runners Ultra high molecular weight polymer Tensile impact 600-1200 ft. lbs. / in²
- - Coefficient of friction .10 ASTM D-1894 Dielectric constant 2.3 ASTM D-150
- The UFRCS1300 provides pipe support only

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

Submitted By:

09/06/23