

SUBMITTAL INFORMATION

40 Series Resetter - (VBB42-xxW-NL style)



ANGLE BALL VALVE BY *ANGLE BALL VALVE (5/8" X 3/4" METER)


METER THREAD INLET AND OUTLET



Resetter Part Number

HEIGHT (INCHES)	APPROX. Wt. Lbs.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
7	3.3	VBB42-7W-NL	
9	3.5	VBB42-9W-NL	
12	3.7	VBB42-12W-NL	
15	3.9	VBB42-15W-NL	
18	4.6	VBB42-18W-NL	
21	4.8	VBB42-21W-NL	
24	5.1	VBB42-24W-NL	
27	5.3	VBB42-27W-NL	
30	5.6	VBB42-30W-NL	

*The Angle Ball Valve is a one-way directional valve designed for the inlet side of the meter and should not be used as a customer shut-off on the customer side of the meter.



Meter Thread Size

INLET	OUTLET	
3/4"	3/4"	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (UNS NO C89833)
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- The product has the letters "NL" cast into the main body for proper identification
- · Saddle nuts hold the meter in place for tightening
- Tie Bar is standard for 18" and taller resetter heights (40 Series)
- Conforms to AWWA C700 for Meter Threads
- 13/16" Copper risers provide more flow capacity
- · All Ford Setters are assembled with lead-free solder
- Copper conforms to ASTM B-75, Copper Alloy #122

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

http://www.fordmeterbox.com 06/22/12

Submitted By: