



SUBMITTAL INFORMATION

80 Series Coppersetter - (VBB82W-22-xx-NL style)



ANGLE BALL VALVE BY *ANGLE BALL VALVE (5/8" x 3/4" METER)

FLARE COPPER INLET AND OUTLET



INLET	OUTLET	APPROX. WT. LBS.	BRACE EYE	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
3/4" Flare Copper	3/4" Flare Copper	5.5	Yes	VBB82W-22-33-NL	
1" Flare Copper	1" Flare Copper	6.3	No	VBB82W-22-44-NL	

* The 5/8" port Angle Ball Valve is a one-way directional valve designed for the inlet side of the meter and should not be used as a customer shut-off on the customer side of the meter.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Copper conforms to ASTM B75 or B88, UNS C12200
- All Ford® Setters are assembled with lead-free solder
- Saddle nuts hold the meter in place for tightening
- 13/16" copper risers provide more flow capacity
- Vertical bracing eye is standard only on the VBB82W-22-33-NL Coppersetter

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

09/08/23

Submitted By: