

SUBMITTAL INFORMATION





ANGLE BALL VALVE BY *ANGLE BALL VALVE (5/8" x 3/4" METER)

QUICK JOINT SWIVEL FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



INLET	OUTLET	APPROX. Wt. Lbs.	Catalog Number	✓ SUBMITTED ITEM(S)
1" Swivel (CTS) Q.J.	1" Swivel (CTS) Q.J.	8.4	VBB82W-44-44-FP-SQ-NL	

^{*} The Angle Ball Valve is a one-way directional valve designed for the inlet side of the meter and should not be used as a customer shut-off on the customer side of the meter.

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Copper conforms to ASTM B75, UNS C12200
- Saddle Nuts hold the meter in place for tightening
- 13/16" Copper Risers provide more flow capacity
- All Ford Setters are assembled with lead-free solder

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

12/09/14

_	•		
Sı	ıhr	nitted	1 Rv