



SUBMITTAL INFORMATION

80 Series Coppersetter - (VBB83W-44-44-NL style)



ANGLE BALL VALVE BY ANGLE BALL VALVE (3/4" METER)

PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



INLET	OUTLET	APPROX. Wt. LBS.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
1" (CTS) P.J.	1" (CTS) P.J.	6.0	VBB83W-44-44-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass components that come in contact with potable water conform to AWWA Standard C800 (UNS NO C89833)
- The product has the letters "NL" cast into the main body for proper identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- Saddle nuts hold the meter in place for tightening
- All Ford Setters are assembled with lead-free solder
- Copper conforms to ASTM B-75, copper alloy #122
- 15/16" copper risers provide more flow capacity
- 1/8" thick meter gaskets are furnished
- The directional angle ball valve shall be rated at 150 psi when used as a customer shut-off on the outlet side of the meter

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443
Phone: 260-563-3171 / Fax: 800-826-3487
Overseas Fax: 260-563-0167
<http://www.fordmeterbox.com>

Submitted By: