


SUBMITTAL INFORMATION





ANGLE BALL VALVE BY ANGLE CARTRIDGE DUAL CHECK VALVE (5/8" X 3/4" METER)


MALE THREADS FOR PACK JOINT ASSEMBLIES INLET AND OUTLET



Coppersetter Part Number

HEIGHT (INCHES)	APPROX. Wt. Lbs.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
9	6.0	VBHC272-9W-NL	
12	6.2	VBHC272-12W-NL	
15	6.4	VBHC272-15W-NL	
18	6.7	VBHC272-18W-NL	
21	7.3	VBHC272-21W-NL	
24	7.6	VBHC272-24W-NL	

Male Threads for Pack Joint Assemblies (PJAx-1x-NL)



Service Line Connection

Please see the Pack Joint Assembly Submittal in Section F (PJAx-1x-NL)



FEATURES

- All brass components that come in contact with potable water conform to AWWA Standard C800 (UNS NO C89833)
- The product has the letters "NL" cast into the main body for proper identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- Saddle Nuts hold the meter in place for tightening
- Two Pack Joint Assemblies required (PJAx-1x-NL) Inlet and Outlet order separately
- Tie Bar is standard for 21" and taller Coppersetter heights (VBHC272 Series)
- 13/16" Copper Risers provide more flow capacity
- · All Ford Setters are assembled with lead-free solder
- Copper conforms to ASTM B-75, Copper Alloy #122
- ASSE 1024 approved cartridge dual check valve

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 http://www.fordmeterbox.com

02/26/14

_			
Sı.	ıhr	nitte	dRv