



# SUBMITTAL INFORMATION

## 90 Series Coppersetter - (VBHC92-xxW-41-33x-G-NL style)




ANGLE BALL VALVE BY ANGLE DUAL CARTRIDGE CHECK VALVE (5/8" X 3/4" METER)

GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY DOUBLE PURPOSE UNION SWIVEL OUTLET



### Options



### Coppersetter Part Number

| HEIGHT (INCHES) | APPROX. WT. LBS. | CATALOG NUMBER         | ✓ SUBMITTED ITEM(S) |
|-----------------|------------------|------------------------|---------------------|
| 15              | 7.5              | VBHC92-15W-41-33x-G-NL |                     |
| 18              | 8.1              | VBHC92-18W-41-33x-G-NL |                     |
| 21              | 8.4              | VBHC92-21W-41-33x-G-NL |                     |
| 24              | 8.7              | VBHC92-24W-41-33x-G-NL |                     |

x = Add option code to catalog number if required. See tables below.

### Option Codes for 90 Series Coppersetters

| OPTION                                   | EXTENSION TO CATALOG NUMBER |
|------------------------------------------|-----------------------------|
| Brace Eye                                | Add "E" to Cat. No.         |
| Bolted Clamp Construction                | Add "C" to Cat. No.         |
| 15" outlet tube extension                | Add "A" to Cat. No.         |
| 15" outlet tube extension & brace eye    | Add "H" to Cat. No.         |
| 15" outlet tube extension & bolted clamp | Add "F" to Cat. No.         |
| 18" outlet tube extension                | Add "B" to Cat. No.         |
| 18" outlet tube extension & brace eye    | Add "K" to Cat. No.         |
| 18" outlet tube extension & bolted clamp | Add "J" to Cat. No.         |

Add extension to catalog number. Example: VBHC92-21W-41-33E-G-NL

### Inlet Tube Options for 90 Series Coppersetters

| OPTION                   | COPPERSETTER SIZE | INLET TUBE OPTION CODE |
|--------------------------|-------------------|------------------------|
| 15" inlet tube extension | 5/8" x 3/4"       | Add "P" to Cat. No.    |
| 18" inlet tube extension | 5/8" x 3/4"       | Add "S" to Cat. No.    |
| Vertical inlet extension | 5/8" x 3/4"       | Add "Z" to Cat. No.    |

Place catalog inlet tube code to the left of any other extension option from the top option table. Example: VBHC92-21W-41-33ZA-G-NL

### Service Line Size

| INLET               | OUTLET           |
|---------------------|------------------|
| 3/4" CTS Grip Joint | 3/4" D.P. Swivel |

**Note:** Ford recommends using insert stiffeners with plastic pipe or tubing.

### FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Copper conforms to ASTM B75 or B88, UNS C12200
- Saddle nuts hold the meter in place for tightening
- Brace eye is optional for all 90 Series Coppersetters with standard solder clamp
- Outlet tube extension and bolted clamp construction are optional on 90 Series
- All Ford® Setters are assembled with lead-free solder
- ASSE 1024 approved cartridge dual check valve
- Double Purpose Union Swivels will accommodate male iron pipe threads or flare copper
- 13/16" copper risers provide more flow capacity

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



**The Ford Meter Box Company, Inc.**  
P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443  
Phone: 260-563-3171 / Fax: 800-826-3487  
Overseas Fax: 260-563-0167  
www.fordmeterbox.com

12/04/18

Submitted By: