

SUBMITTAL INFORMATION





ANGLE BALL VALVE BY ANGLE DUAL CHECK VALVE (2" METER)

GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



SERVICE LINE CONNECTION		HEIGHT	Approx.	CATALOG NUMBER	✓ SUBMITTED
CTS GJ INLET	CTS GJ OUTLET	ПЕІВНІ	Wt. Lbs.	CAIALOG NUMBER	ITEM(S)
2"	2"	12"	32	VBHH77-12B-44-77-G-NL	
		15"	33	VBHH77-15B-44-77-G-NL	
		18"	34	VBHH77-18B-44-77-G-NL	
		21"	34	VBHH77-21B-44-77-G-NL	
		24"	35	VBHH77-24B-44-77-G-NL	
		27"	35	VBHH77-27B-44-77-G-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Copper conforms to ASTM B75 or B88, UNS C12200
- All Ford® Setters are assembled with lead-free solder
- · Bracing eyes are standard
- Meter support brackets are standard
- Optional high bypass add "HB" following the height. Example: VBHH77-12HB-44-77-G-NL
- Padlock wing is standard on all angle meter ball valves or key valves
- Dual check valve is ASSE 1024 approved

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

06/15/22

	nitte	