

SUBMITTAL INFORMATION





ANGLE KEY VALVE BY ANGLE CHECK VALVE (2" METER)

QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET AND OUTLET



SERVICE LINE CONNECTION (IN.)		HEIGHT (IN)	Approx.	CATALOG NUMBER	✓ SUBMITTED
CTS QJ INLET	CTS QJ OUTLET	HEIGHT (IN.)	Wt. Lbs.	CAIALOG NUMBER	ITEM(S)
2	2	12	32	VH77-12-44-77-Q-NL	
		15	33	VH77-15-44-77-Q-NL	
		18	34	VH77-18-44-77-Q-NL	
		21	34	VH77-21-44-77-Q-NL	
		24	35	VH77-24-44-77-Q-NL	
		27	35	VH77-27-44-77-Q-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification.
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Certified to NSF/ANSI/CAN Standard 61 and NSF/ANSI/CAN Standard 372 where applicable
- Copper conforms to ASTM B75 or B88, UNS C12200
- All Ford® Setters are assembled with lead-free solder
- · Bracing eves are standard
- · Meter support brackets are standard
- Optional Bottom Bar Bypass add "B" following the height. Example: VH77-12B-44-77-Q-NL
- Optional High Bypass add "HB" following the height. Example: VH77-12HB-44-77-Q-NL
- Padlock wing is standard on all Angle Meter Ball Valves or Key Valves

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current. Our standard warranty applies.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

07/24/24

ubmitted By:		