

# SUBMITTAL INFORMATION






ANGLE KEY VALVE BY ANGLE CARTRIDGE DUAL CHECK VALVE (5/8" X 3/4" METER)

### MALE IRON PIPE UNION SWIVEL INLET BY DOUBLE PURPOSE UNION SWIVEL OUTLET



• •			
Неіднт	Approx.	CATALOG NUMBER	✓ SUBMITTED
(INCHES)	WT. LBS.	(INSERT SERVICE LINE CONN. SIZE)	ITEM(S)
9	6.2	VHC72-9W-81-xx-NL	
12	6.4	VHC72-12W-81-xx-NL	
15	6.6	VHC72-15W-81-xx-NL	
18	7.3	VHC72-18W-81-xx-NL	
21	7.5	VHC72-21W-81-xx-NL	
24	7.8	VHC72-24W-81-xx-NL	
27	8.0	VHC72-27W-81-xx-NL	
30	8.3	VHC72-30W-81-xx-NL	
33	8.6	VHC72-33W-81-xx-NL	
36	8.8	VHC72-36W-81-xx-NL	
39	9.1	VHC72-39W-81-xx-NL	

**Coppersetter Part Number** 



## **Service Line Size**

VHC72-42W-81-xx-NL

INLET	OUTLET	SERVICE LINE CONN. SIZE	✓ SUBMITTED  ITEM(S)
3/4" MIP Swive	I 3/4" D.P. Swivel	33	
1" MIP Swive	1" D.P. Swivel	44	

### **FEATURES**

 All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)

42

9.4

- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Copper conforms to ASTM B75, Copper Alloy UNS C12200
- Saddle nuts hold the meter in place for tightening
- Bracing eye is standard on all 70 Series Coppersetters
- Tie bar is standard for 21" and taller Coppersetter heights (VHC72 Series)
- Double Purpose Union Swivels will accommodate male iron pipe threads or flare copper
- 13/16" copper risers provide more flow capacity
- All Ford Setters are assembled with lead-free solder.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



# The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

05/02/16

Submitted By: