


SUBMITTAL INFORMATION





ANGLE KEY VALVE BY ANGLE CARTRIDGE DUAL CHECK VALVE (1" METER)

FLARE COPPER INLET AND OUTLET



Inlet	OUTLET	APPROX. Wt. Lbs.	CATALOG NUMBER	✓ SUBMITTED ITEM(S)
1" Flare Copper	1" Flare Copper	10.5	VHC84W-22-44-NL	

FEATURES

- All brass components that come in contact with potable water conform to AWWA Standard C800 (UNS NO C89833)
- The product has the letters "NL" cast into the main body for proper identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- Saddle Nuts hold the meter in place for tightening
- 1-1/8" Copper Risers provide more flow capacity
- All Ford Setters are assembled with lead-free solder
- Full Port Cartridge Dual Check Valve is ASSE 1024 approved
- Copper conforms to ASTM B-88, Copper Alloy #122

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 http://www.fordmeterbox.com

01/28/14

_			
Sı.	ıhr	nitte	dRv