


# SUBMITTAL INFORMATION






### ANGLE KEY VALVE BY ANGLE KEY VALVE (5/8"x3/4" METER)

#### METER THREAD INLET AND OUTLET



#### **Resetter Part Number**

HEIGHT (INCHES)	APPROX. Wt. Lbs.	CATALOG NUMBER	✓ SUBMITTED  ITEM(S)
7	4.8	VV42-7W-NL	
9	5.0	VV42-9W-NL	
12	5.2	VV42-12W-NL	
15	5.4	VV42-15W-NL	
18	6.1	VV42-18W-NL	
21	6.3	VV42-21W-NL	
24	6.6	VV42-24W-NL	
27	6.8	VV42-27W-NL	
30	7.1	VV42-30W-NL	



#### **Meter Thread Size**

INLET	OUTLET	
3/4"	3/4"	

#### **FEATURES**

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (UNS NO C89833)
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- The product has the letters "NL" cast into the main body for proper identification
- Saddle nuts hold the meter in place for tightening.
- Tie Bar is standard for 18" and taller resetter heights (40 Series).
- · Conforms to AWWA C700 for Meter Threads.
- 13/16" Copper risers provide more flow capacity.
- All Ford Setters are assembled with lead-free solder.
- Copper conforms to ASTM B-75, Copper Alloy #122.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



## The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 http://www.fordmeterbox.com

06/27/12

Submitted By: