


SUBMITTAL INFORMATION





GRIP JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY FEMALE IRON PIPE THREAD OUTLET

STRAIGHT BALL VALVE BY STRAIGHT CARTRIDGE DUAL CHECK VALVE OUTLET



METER	CTS GJ	FIP	APPROX.	CATALOG	✓ SUBMITTED ITEM(S)
Size	INLET	OUTLET	Wt. Lbs.	Number	
5/8" x 3/4"	3/4"	3/4"	29.0	YSBHC141-233-LL-T-G-NL	

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Base, upper section and lid are cast iron per ASTM A48, Class 25 with black e-coat
- The brass end fittings are permanently and properly spaced and aligned for the meter
- ASSE 1024 approved cartridge dual check valve
- Lockless lid with 2" hole for electronic meter reading module

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

02/12/15

_			
Sı.	ıhr	nitte	dRv